

Spectrum®

PRODUCT

Catalogue

ATURAN PENYIMPANAN:

- Kemasan cat ini harus selalu tertutup rapat dan jauhkan dari jangkauan anak-anak.
- Jauhkan dari makanan, minuman dan makanan hewan karena berbahaya jika tertelan.
- Kemasan ini hanya dapat digunakan untuk menyimpan cat.
- Simpan cat ditempat yang sejuk dan kering.
- Jangan menyimpan cat dengan posisi tergantung pada cantelanemasannya.
- Jaga agar kemasan cat dalam keadaan berdiri.
- Bila sudah digunakan, tutuplah kaleng cat dengan rapat sebelum penyimpanan.

INFORMASI KESELAMATAN, KEAMANAN, KESEHATAN KERJA DAN LINGKUNGAN HIDUP (4KLH):

- Cat ini tidak mengandung bahan: merkuri, timbal, formalin dan kadmium.
- Cat ini berbahan dasar air dan tidak menggunakan bahan dasar epoksi.
- Bebas kandungan kimia berbahaya serta memiliki kadar VOC, APEO dan uap organik (bau) yang sangat rendah.
- Selama pengecatan dan proses pengeringan cat harus dipastikan ada ventilasi udara yang baik.
- Dianjurkan memakai alat pelindung mata selama pengecatan.
- Apabila terkena mata, bilaslah dengan air bersih, bila perlu periksakan ke dokter.
- Sebaiknya gunakan juga sarung tangan selama pengecatan.
- Aduklah cat dengan alat bantu, jangan menggunakan tangan secara langsung.
- Cuci atau bersihkan cat yang menempel pada kulit dengan sabun dan air.
- Cuci semua peralatan atau perlengkapan cat dengan air bersih.
- Jangan menghirup uap produk atau semprotan secara langsung.
- Jangan membuang sisa cat ke selokan atau anak sungai demi menjaga kebersihan lingkungan.
- Buanglah sisa cat pada tempat yang telah diijinkan menurut peraturan yang ada.
- Bila cat tumpah, taburkan pasir atau tanah pada daerah yang tertumpah lalu bersihkan.



www.sci-paint.com

Diproduksi oleh:



PT. SAN CENTRAL INDAH
Bandung - Indonesia.



UltraProtection

MORE THAN JUST COLOR

Spectrum® System Painting

Langkah 1

Tembok Baru

- Bersihkan acian & kotoran.
- Pengeringan tembok minimal 30 hari.
- Protimeter berkisar <math>< 16\%</math> dengan $\text{pH} < 9$

Tembok Lama

- Jika lapisan cat lama masih baik bersihkan dengan air bertekanan tinggi, dan jika terdapat jamur atau lumut, cuci dan bersihkan dengan larutan 1 liter pemutih dalam 3 liter air bersih.
- Jika lapisan cat lama sudah mengapur dan mengelupas, kerok seluruh lapisan cat hingga bersih dan pastikan tembok benar-benar kering.

Langkah 2

- Untuk tembok baru dan cat lama yang dikerok, beri dua lapis Spectrum UltraPrimer.
- Untuk cat lama yang masih baik, beri satu lapis Spectrum Alkali Resisting Primer.



Langkah 3

- Jika ada retak rambut aplikasikan Plamur hanya pada bagian tersebut*

- Jika tidak ada retak rambut.

Langkah 4

- Beri satu lapis Spectrum Alkali resisting Primer pada bagian yang terkena Plamur saja.



Langkah 5

- Aplikasikan Spectrum UltraShield/ Spectrum Interior - Exterior.



*PERHATIAN

Jangan gunakan plamur (Wall Filler) sebagai cat dasar tetapi gunakan Spectrum: UltraPrimer/Alkali Resisting Primer sebagai cat dasar.



Spectrum®

protection from all weather conditions

NEW PRODUCT



UltraShield

protection from all weather conditions

- Specialist Exterior Paint
- Anti Fungus & Algae
- Fade Resistance Color
- Excellent Adhesion
- Weather Resistance
- Satin finish Paint

Description :

•Ultra protection from all weather conditions with long lasting color and beautiful satin finish for exterior wall paint.

Typical Uses :

•Recommended for walls, ceiling, and trim. Use on wallboard or drywall, primed plaster, concrete, brick, and wallpaper. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For exterior applications.

Characteristics :

Vehicle Type	: Acrylic
Finish	: Satin
Colors	: White and over 640 customs colors
Weight/liter	: 1.2-1.40 Kg/liter
Solids	: Volume 36-40%, Weight: 45 - 55%
Viscosity	: 95-99 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 30-45 minutes
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Coverage	: 20-25 m ² /gallon (substrate dependent)
Tinting	: Available with San Color Colorant

Application :

•Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



UltraProtection



Spectrum®

UltraPrimer

protection from all weather conditions



all-in-one Superior Protection

- Water-Based
- Maximum Protection against alkali and moisture
- Adding Paint Adhesion and Maximum Durability
- Excellent Adhesion
- Weather Resistance

Description :

•A high performance water based primer designed to protect the finish against alkali, chalking, and efflorescence.

Typical Uses :

•Recommended for walls. Use on wallboard or drywall, primed plaster, concrete, brick, and wallpaper. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For interior and exterior applications.

Characteristics :

Vehicle Type	: Acrylic
Finish	: Satin
Colors	: White
Weight/liter	: 1.17-1.19 Kg/liter
Solids	: Volume 46-48%, Weight: 54 - 56%
Viscosity	: 88-95 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 3-4 hours
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Cured Time	: 24 hours
Coverage	: 25-30 m ² /gallon (one coat application)

Application :

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.






UltraProtection






New Residential coating system




KAMAR TIDUR

-  cat dasar alkali resisting primer
-  cat tembok interior - exterior
-  gypsum paint

KAMAR MANDI

-  cat dasar UltraPrimer
-  cat tembok interior - exterior
-  gypsum paint



RUANG TAMBAHAN

-  cat dasar alkali resisting primer
-  cat tembok interior - exterior
-  gypsum paint




EKSTERIOR/LUAR

-  cat dasar UltraPrimer
-  cat tembok exterior UltraShield
-  cat dasar alkali resisting primer
-  cat tembok interior - exterior




GARASI

-  cat dasar alkali resisting primer
-  cat tembok interior - exterior

RUANG KELUARGA

-  cat dasar alkali resisting primer
-  cat tembok interior - exterior
-  gypsum paint

DAPUR

-  cat dasar UltraPrimer
-  cat tembok interior - exterior
-  gypsum paint

EKSTERIOR/LUAR

-  cat dasar UltraPrimer
-  cat tembok exterior UltraShield
-  cat dasar alkali resisting primer
-  cat tembok interior - exterior



Spectrum[®]
MORE THAN JUST COLOR



Specialist Exterior Paint



UltraPrimer



Interior-Exterior paint



Alkali Resisting Primer



Gypsum Paint



INTERIOR EXTERIOR PAINT

- Good coverage and hiding power
- Excellent color fastness
- Eco-friendly with low VOC and low odor
- Durable, washable, and scrubbable
- Smooth matte flat finish and fast dry
- Soap and water cleanup
- Anti fungus and algae



Description :

- A high performance fast-drying water based adhesion and a beautiful smooth matt finish for interior and exterior wall paint.

Typical Uses :

- Recommended for walls, ceiling, and trim. Use on wallboard or drywall, primed plaster, concrete, brick, and wallpaper. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For interior and exterior.

Characteristics :

Vehicle Type	: Styrene Acrylic
Finish	: Matte Flat
Colors	: White and over 640 customs colors
Weight/liter	: 1.35-1.65 Kg/liter
Solids	: Volume 34-39%, Weight: 50 - 60%
Viscosity	: 90-98 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 30-45 minutes
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Coverage	: 20-25 m ² /gallon (substrate dependent)
Tinting	: Available with San Color Colorant

Application :

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



ALKALI RESISTING PRIMER

- Alkali resistant
- Highly durable and resistant to weathering
- Good adhesion property
- Can be used to prime marginally cured concrete
- Used under water based paints
- Interior and exterior



Description :

- A high performance water based primer designed to protect the finish against alkali, chalking, and efflorescence.

Typical Uses :

- Recommended for walls. Use on wallboard or drywall, primed plaster, concrete, brick, and wallpaper. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For interior and exterior applications.

Characteristics :

Vehicle Type	: Styrene Acrylic
Finish	: Matte Flat
Colors	: White
Weight/liter	: 1.23-1.30 Kg/liter
Solids	: Volume 31-33%, Weight : 44-46%
Viscosity	: 90-98 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 30-45 minutes
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Coverage	: 40-50 m ² /gallon (substrate dependent)
Tinting	: not Available

Application :

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.





GYPSUM PAINT

- Specialist Gypsum Paint
- Very good hiding
- Easy to use
- Matte flat finish hides minor ceiling imperfections
- Non-yellowing

Description :

- High quality ceiling paint. Especially formulated for gypsum board, drywall and other ceiling materials.

Typical Uses :

- Recommended for gypsum board, drywall, plywood and other ceilings materials. Use in homes, schools, offices, hospitals, condominiums, commercial properties, etc. Not intended for exterior applications.

Characteristics :

Vehicle Type	: Styrene Acrylic
Finish	: Matte Flat
Colors	: White
Weight/liter	: 1.60-1.62 Kg/liter
Solids	: Volume 37-39%, Weight: 60-62%
Viscosity	: 90-98 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 30-45 minutes
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Coverage	: 20-25 m ² /gallon (substrate dependent)
Tinting	: Available with San Color Colorants

Application :

- Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



PROTECTION
FOR ALL WEATHER
CONDITION



MORE
THAN
JUST
COLOR



GREEN
SOLUTION

100%
INDONESIA