



Dutch Boy

# Kem-Tone

## Technical Data Sheet

022/TDS/SCI/VIII/2019



www.sci-paint.com

### Exterior Satin Finish Paint



**Exterior Satin Finish Paint**  
A premium 100% acrylic exterior wall and trim paint.

#### Features:

- Excellent hiding
- Extended chalk resistant
- Long term durability
- Extended weather resistant
- Excellent fade resistant and adhesion
- Soap and water cleanup

#### Description:

A premium 100% acrylic exterior wall and trim paint.

#### Typical Uses:

Recommended for walls and trims. Use on primed plaster, wood, concrete, brick and primed metal. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For exterior applications.

#### Characteristics:

Vehicle Type

Finish

Colors

Weight/liter

Solids

Viscosity

pH

Drying Time (to touch)\*

Drying Time (to recoat)\*

\* @ 25°C & 50% R.H.

Coverage

Tinting

: Acrylic Emulsion

: Satin, 5-15 units @ 85°

: White and over 1,000 customs colors

: 1.30 - 1.40 Kg/liter

: Volume 41.5 - 42.5%, Weight: 52 - 53%

: 92 - 100 KU

: 8.5 - 9.0

: 30 minutes

: 4 hours

: 20 - 25 m<sup>2</sup> per-gallon (substrate dependent)

: Available with San Color Colorant

#### Application:

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



Dutch Boy

# Kem-Tone

## Technical Data Sheet

022/TDS/SCI/VIII/2019



www.sci-paint.com

### Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not hang paint can on the can hook.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

### Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This paint is water based and does not use epoxy based ingredients.
- Free of hazardous chemicals and have very low levels of VOC and odor.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Wash all equipment or supplies with clean water after painting.
- Do not breathe product or spray directly.
- Use a nose mask when flattening walls, removing old paint and when painting.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



### COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: [info@sci-paint.com](mailto:info@sci-paint.com); Website: [www.sci-paint.com](http://www.sci-paint.com)

