



scipaint

Spectrum[®]

interior - exterior paint

Technical Data Sheet

010/TDS/SCI/VIII/2019



www.sci-paint.com

DESCRIPTION

A high performance fast-drying water based adhesion and a beautiful smooth matt finish for interior and exterior wall paint.

FEATURES

- Good coverage and hiding power
- Excellent color fastness
- Eco-friendly with low VOC and low odor
- Durable, washable, and scrubbable
- Smooth matte flat finish and fast dry
- Soap and water cleanup
- Anti fungus and algae
- Satin finish Paint

TYPICAL USES

Recommended for walls, ceiling, and trim. Use on wallboard or drywall, primed plaster, concrete, brick, and wallpaper. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For interior and exterior.

CHARACTERISTICS

Vehicle Type	: Styrene Acrylic
Finish	: Matte Flat
Colors	: White and over 640 customs colors
Weight/liter	: 1.35-1.65 Kg/liter
Solids	: Volume 34-39%, Weight: 50 - 60%
Viscosity	: 90-98 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 30-45 minutes
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Coverage	: 20-25 m ² /gallon (substrate dependent)
Tinting	: Available with San Color Colorant

APPLICATION

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



scipaint

Spectrum[®]

interior - exterior paint

Technical Data Sheet

010/TDS/SCI/VIII/2019



www.sci-paint.com

Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not hang paint can on the can hook.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This paint is water based and does not use epoxy based ingredients.
- Free of hazardous chemicals and have very low levels of VOC and odor.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Wash all equipment or supplies with clean water after painting.
- Do not breathe product or spray directly.
- Use a nose mask when flattening walls, removing old paint and when painting.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: info@sci-paint.com; Website: www.sci-paint.com

