



Dutch Boy

Kem-Tone

Technical Data Sheet

025/TDS/SCI/VIII/2019



www.sci-paint.com

Wall Sealer

Features:

- Alkali resistant
- Can be used to seal and prime weathered and chalky surfaces
- Breathing film without adhesion loss from the substrate
- Provide excellent adhesion and highly durable
- Used under latex or oil (solvent based paints)
- Highly durable



Description:

High quality solvent based wall sealer.

Typical Uses:

Recommended for sealing and priming painted and unpainted surfaces. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For interior and exterior applications.

Characteristics:

Vehicle Type	: Acrylic Ester Copolymer
Finish	: N/A
Colors	: Clear
Weight/liter	: 7.46 lbs/gallon
Solids	: Volume 14.62%, Weight: 18.02%
Viscosity	: A3 Gardner
pH	: N/A
Drying Time (to touch)*	: 1 hour
Drying Time (to recoat)*	: 8 hours
* @ 25°C & 50% R.H.	
Coverage	: 45 - 50 m ² per-gallon (substrate dependent)
Tinting	: Not Available

Application:

Use roll, brush or airless spray. Paint at temperature above 10°C.



Dutch Boy

Kem-Tone

Technical Data Sheet

025/TDS/SCI/VIII/2019



www.sci-paint.com

Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not store paint in an upside down position.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This oil-based paint and keep it away from fire, because it is flammable.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Clean all paint equipment or supplies after painting.
- Do not breathe product or spray directly.
- Use a nose mask to paint.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: info@sci-paint.com; Website: www.sci-paint.com

