



scipaint



Dutch Boy

Kem-Tone

Technical Data Sheet

023/TDS/SCI/VIII/2019



www.sci-paint.com

Gypsum & Ceiling Paint

Features:

- Very good hiding
- Water cleanup
- Easy to use spatter resistant formulation
- Matt flat finish hides minor ceiling imperfections
- Non-yellowing
- One coat application



Description:

High quality latex ceiling paint. Especially formulated for gypsum board, drywall and other ceiling materials.

Typical Uses:

Recommended for gypsum board, drywall, plywood and other ceilings materials. Use in homes, schools, offices, hospitals, condominiums, commercial properties, etc. **Not intended for exterior applications.**

Characteristics:

Vehicle Type	: Vinyl VeOVa
Finish	: Matte Flat, 0-10 units @ 85°
Colors	: Bright White
Weight/liter	: 1.60 - 1.70 Kg/liter
Solids	: Volume 41 - 42%, Weight: 63 - 64%
Viscosity	: 90 - 98 KU
pH	: 8.5 - 9.0
Drying Time (to touch)*	: 30 minutes
Drying Time (to recoat)*	: 4 hours
* @ 25°C & 50% R.H.	
Coverage	: 20 - 25 m ² per-gallon (substrate dependent)
Tinting	: Available with San Color Colorant

Application:

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



scipaint



Dutch Boy

Kem-Tone

Technical Data Sheet

023/TDS/SCI/VIII/2019



www.sci-paint.com

Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not hang paint can on the can hook.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This paint is water based and does not use epoxy based ingredients.
- Free of hazardous chemicals and have very low levels of VOC and odor.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Wash all equipment or supplies with clean water after painting.
- Do not breathe product or spray directly.
- Use a nose mask when flattening walls, removing old paint and when painting.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: info@sci-paint.com; Website: www.sci-paint.com

